

## ECONTROL COMFORT I



Control Panel for the automatic operation of 1 x Pump

ECONTROL COMFORT 230/I  
Voltage: 1~230V - 50 Hz

ECONTROL COMFORT 400/I  
Voltage: 3~400V - 50 Hz

Type	max. Pump kW	Current A	Art. No.
ECONTROL COMFORT 230/I	0.37	2.5 - 4.0	6430000380
ECONTROL COMFORT 230/I	0.75	4.0 - 6.3	6430000382
ECONTROL COMFORT 230/I	1.1 kW	6.3 - 10.0	6430000383
ECONTROL COMFORT 230/I	2.2 kW	10.0 - 16.0	6430000385
ECONTROL COMFORT 400/I	0.75	1.6 - 2.5	6430001166
ECONTROL COMFORT 400/I	1.1 kW	2.5 - 4.0	6430001249
ECONTROL COMFORT 400/I	2.2 kW	4.0 - 6.3	6430001031
ECONTROL COMFORT 400/I	4.0	6.3 - 10.0	6430000388
ECONTROL COMFORT 400/I	5.5 kW	10.0 - 16.0	6430000837

Dimensions: 318 x 267 x 167 mm (Cover Material: glass-fibre-reinforced)

- Automatic operation with connected pressure-switch or float-switch
- Manual operation possible
- LED Display: 1 x Operation (green) and 1 x Malfunction/Error (red)
- Cable connections: 3 x M20 & 3 x M25  
(supply, pump, float-switch (dry-run), pressure-switch/float-switch, alarm acoustic/optical)
- + Alarm Exit: potential-free contact for Central Building Control System (max. 230 V/4.0 A)
- ON/OFF Switch – lockable mains switch
- Overload Protection, Short Circuit Protection, Phase-malfunction protection
- dry-running protection via external device (float-switch)
- Connection possibility for external Alarm (Light/Buzzer)