



Product Service

CERTIFICATE

No. Z1A 015912 0052 Rev. 00

Holder of Certificate: **Ebara Pumps Europe S.p.A.**

Via Campo Sportivo 30
38023 Cles (TN)
ITALY

Certification Mark:



Product: **Submerged pump**

Tested according to: EN 60335-2-41:2003/A2:2010
EN 60335-1:2012/A14:2019
AfPS GS 2019:01 PAK
EN 62233:2008

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: ELS1586015A

Valid until: 2026-03-16

Date, 2021-03-24

(MASSIMO MENDO)

ZERTIFIKAT ◆ CERTIFICATE ◆ 認 證 證 書 ◆ CERTIFICADO ◆ CERTIFICAT



CERTIFICATE

No. Z1A 015912 0052 Rev. 00

Model(s):

BEST 2 CABLE H07RN8-F	– cod. 1721094604
BEST 2M A CABLE H07RN8-F	– cod. 1721094621
BEST 2M CABLE H07RN8-F	– cod. 1721094721
BEST 3 CABLE H07RN8-F	– cod. 1721104604
BEST 3M A CABLE H07RN8-F	– cod. 1721104621
BEST 3M CABLE H07RN8-F	– cod. 1721104721
BEST 4 CABLE H07RN8-F	– cod. 1731154604
BEST 4M A CABLE H07RN8-F	– cod. 1731154621
BEST 4M CABLE H07RN8-F	– cod. 1731154721
BEST 5 CABLE H07RN8-F	– cod. 1731204604

Brand Name:

EBARA

Rated input voltage:	230-240 VAC 1ph, 400-415 VAC 3ph
Rated frequency:	50 Hz
Rated input power:	See table
Rated input current:	See table
Maximum water temperature:	35 °C
Maximum submersion depth:	See table
Protection class:	I
Degree of protection:	IP68



Product Service

CERTIFICATE

No. Z1A 015912 0052 Rev. 00

Code	Model	Rated Voltage	Rated Power (P1) [kW]	Rated current [A]	Max head [m]	Min head [m]	Maximum depth [m]
1721094604	BEST 2 CABLE H07RN8-F	400-415 V 3ph	1.0	2	13.1	2.9	7
1721094621	BEST 2M A CABLE H07RN8-F	230-240 V	0.98	4.4	13.1	2.9	7
1721094721	BEST 2M CABLE H07RN8-F	230-240 V	0.98	4.4	13.1	2.9	7
1721104604	BEST 3 CABLE H07RN8-F	400-415 V 3ph	1.2	2.4	14.6	3.2	7
1721104621	BEST 3M A CABLE H07RN8-F	230-240 V	1.3	5.6	14.6	3.2	7
1721104721	BEST 3M CABLE H07RN8-F	230-240 V	1.3	5.6	14.6	3.2	7
1731154604	BEST 4 CABLE H07RN8-F	400-415 V 3ph	1.6	3.0	18	4.6	7
1731154621	BEST 4M A CABLE H07RN8-F	230-240 V	1.65	7.3	18	4.6	7
1731154721	BEST 4M CABLE H07RN8-F	230-240 V	1.65	7.3	18	4.6	7
1731204604	BEST 5 CABLE H07RN8-F	400-415 V 3ph	1.7	3.3	19	5	7

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICATE